

FALL 2020



Composites Connection[™]

Official Newsletter of the SPE Composites Division Reaching Over 1,000 Composites Professionals In All Industries



Sponsored by:











E. BRIGHTER LIVING

DSM







Composites Connection™

Advancing Composites Technology Worldwide

Sept/Oct 2020



Chairman's Message:



Ian Swentek, Ph.D.

omposite materials continue to grow in demand and application. Likewise, our division is growing, responding, and pioneering how we support the varied academics and industrial professionals driving these developments. We are the premier professional society focused on the science, engineering, manufacturing, and application of all types of reinforced polymer composites. That last statement was taken directly from our revised vision statement and mirrors the future-thinking that undergirds our organization.

In reflecting on our short, four-decade history, we must adapt to the realities of a maturing workforce and the priorities of a new generation of young professionals. We continue to champion universal equality through our outreach, education, and award programs. Our mission (in brief) remains steadfast: to educate and promote the benefits of reinforced polymers composite materials and to recognize member achievements in research, development, and commercialization of materials, processes, and products. Our world has recently experienced events (namely SARS-CovV-2) that have pushed many people to adapt remote working protocols – we have therefore temporarily pivoted to virtual conferencing, but look forward to restoring the strong interpersonal network within our society. Over the coming months, further changes are anticipated as we strive to modernize our modes of communication and bring further value to each member of the division.

If you would like to contribute your time or talent to the Composite Division in a more substantial way, please reach out to myself or any member of our board. We are always on the lookout for folks with different skills who are passionate about this field.

Autot

Dr. Ian Swentek SPE Composite Division Chair 2019-2021

















🙏 MITSUBISHI CHEMICAL

Board of Directors





lan Swentek, Ph.D. SPE Composites Director, Chair & Auditing Committee Chair Applications Development Engineer Hexion London, ON, Canada Ian.Swentek@hexion.com



Ray G. Boeman, Ph.D. SPE Composites Director, & Memebership Chair Director, Vehicle Technology Area Michigan State University Detroit, MI



Antoine Rios, Ph.D. SPE Composites Director & Finance Chair The Madison Group Madison, WI Antoine@madisongroup. com



John P. Busel, F. ACI SPE Composites Director, Intersociety Chair & Chair-Elect V.P. Composites Growth Initiative American Composites Manufacturers Association Arlington, VA busel@armanet.org



Tim Johnson SPE Composites Director & Treasurer Owner, President at TJohnson LLC Dayton, OH TJohnsonLLC@gmail.com



Dale Brosius SPE Composites Director & Councilor Chief Commercialization Officer, IACMI Knoxville, TN dbrosius@iacmi.org



Uday Vaidya, Ph.D. SPE Composites Director & Education Chair Professor in Mechanical, Aerospace & Biomedical Engineering Chief Technology Officer (CTO), IACMI University of Tennessee Knoxville, TN uvaidva@utk.edu



Hicham Ghossein, Ph.D. SPE Composites Director & Award Chair President & Founder of Endeavor Hicham.ghossein@ gmail.com

This Issue:

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report





Pritam Das SPE Composites Director & Newsletter Chair Senior Technical Manager Toray Composites Materials America (CMA) Tacoma, WA pdas@toraytca.com



Dale Grove, Ph.D. SPE Composites Director & Award Chair US Silica Senior Technology Product Development Berkeley Springs, WV grove.dale@hotmail.com



Andrew Rich SPE Composites Director & Communications Chair Consultant elvamk5@comcast.net



Shankar Srinivasan, Ph.D. SPE Composites Director & ANTEC Program Chair Iowa State University Economic Development Core Facility Ames, IA srigshan@iastate.edu



Engineering plastics and polyurethanes by BASF for the automotive industry

We turn your ideas into ideal solutions: BASF plastics for the automotive industry.

Shorter development times, enhanced performance, greater freedom in design. You do not want to settle for anything less than the perfect car. Neither do we. That is why we will stay by your side at every stage of your project with our comprehensive expertise in plastics and application development, individual parts testing, consultancy in design, simulation and much more - available to you around the world. When your idea turns into the ideal car, it's because at BASF, we create chemistry.

www.performance-materials.basf.com

Board of Directors continued...





Oleksandr G. Kravchenko, Ph.D. SPE Composites Director, ACCE Technical Program Co-Chair, & Assistant Professor,Dept. of Mechanical and Aerospace Engineering Old Dominion University Norfolk, VA okravche@odu.edu



Rich Caruso SPE Composites Director CEO Inter/Comp LLC Falmouth, MA rpcaruso@gmail.com



Michael Connolly, Ph.D. SPE Composites Director Program Manager-Urethane Composties Huntsman Polyurethanes Auburn Hills, MI michael_connolly@hunts man.com



Frederick S. Deans SPE Composites Director Principal Allied Composite Technologies, LLC Rochester Hills, MI fdeans@alliedcomptech. com



Jack Gillespie, Ph.D. SPE Composites Director Director, Center for Composite Materials Donald C. Phillips Professor of Civil and Environmental Engineering University of Delaware Newark, DE gillespi@udel.edu



Jim Griffing SPE Composites Director & SPE Past President Boeing (Retired) Seattle, WA jsgriff1@gmail.com



Enamul Haque, Ph.D. SPE Composites Director A2H Consulting Group Enamul.Haque@ a2hconsultinggroup.com



Daniel T. Buckley SPE Composites Director (Retired) Emeritus Director

This Issue:

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report

Sponsor the Newsletter

The best advertising value in the Composites Industry

- Support your SPE Composites Division
- Reach 1,000 Composites Professionals 3 Times a year via the E-Newsletter
- Maximize your exposure to the customers & the trade



Board of Directors continued...





Christoph Kuhn SPE Composites Director Volkswagen Group Research Materials & Manufacturing Methods Wolfsburg, Germany christoph.kuhn@ volkswagen.de



Marcos Pantoja, Ph.D. SPE Composites Director & Next Generation Advisory Board (NGAB) Liaison Materials and Process Engineer The Boeing Company St. Louis, MO marcos.pantoja @boeing.com



Khaled W. Shahwan, Ph.D. SPE Composites Director Sr. Technology Leader -Composites, Methods & Strategies, Fiat Chrysler Automobiles (Innovation & Adv. Engineering) Auburn Hills, MI khaled.shahwan @fcagroup.com



Mingfu Zhang, Ph.D. SPE Composites Director Johns Manville Research Manager, Corporate R&D Littleton, CO mingfu.zhang@jm.com



closing the loop - loday and tomorraw

Introducing the re-Evo® brand of products



Our family of chopped carbon fiber products are ideal for thermoplastic compounding and injection molding.

Our family of non-woven products are ideal for closed/open mold infusion, pre-preg, and compression molding.



Contact us today & join the recycling Evolution for Carbon Fiber

(843) 374-5600

www.carbonconversions.com

Composites Connection

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report



Materials. Process. Design. Building Lighter and Safer Cars for Tomorrow.

Forged Molding Compound

The NEW Look of Carbon Fiber Carbon Fiber Thermoset Composites

SymaLITE[®]

Low Weight Reinforced Thermoplastics (LWRT) Composite Materials

KyronMAX[™]

Advanced Chopped Carbon Fiber Engineering Thermoplastic Compounds: PA, PPA, PPS, PEI, PEAK, PAEK GMT

Glass Mat Reinforced Thermoplastics

GMTex[®] Structural Thermoplastic Composite Materials

FUNCSTER[™] Long Glass Fiber Polypropylene Composites



MITSUBISHI CHEMICAL CARBON FIBER AND COMPOSITES





Mitsubishi Chemical and our group companies are dedicated to the automotive industry, with R&D and growth in high performance composites aimed at interior, exterior and functional applications. Our focus is on developing and bringing to market lightweight, sustainable, high value and premium asthetic solutions. Look to Mitsubishi Chemical for the ultimate in range, innovation and value.



mitsubishi-chemical.com

Board Meeting Minutes March 17, 2020



By: John P. Busel

SPE Composites Division Board of Directors Meeting

Tuesday, March 17, 2020 12:00 PM – 1:00 PM Eastern US Conference Call

1. Welcome

- Ian Swentek called the meeting to order at 12:01 pm.
- John Busel conducted the Roll Call.

2. Administrative

• Ian Swentek reviewed the last meeting minutes of December 3, 2019 and January

14, 2020 meetings. John Busel made a correction to the spelling for Khaled Shahwan. Ian Swentek moved to accept the minutes as revised. Motion was seconded. Motion passed unanimously. January 14, 2020. Ian Swentek moved to accept the minutes as written. Motion passed unanimously.

• Ian Swentek reviewed the action items from the last meeting (see attachment 1).

continued on page 9...



Board Meeting Minutes continued...



ABARIS

TRAINING

Leading the World in Advanced Composite Training Since 1983!

• Ian Swentek reviewed the proposed revised mission statement. Ian Swentek solicited additional comments and changes to the mission statement. Only one comment was received. The proposed revised vision/mission statement is as follows:

Proposed vision statement:

The SPE Composites Division strives to be the premier professional organization focused on the science, engineering, and application of all types of polymer composites.

Proposed mission statement:

The mission of the SPE Composites Division is to promote the benefits of polymer composite materials, provide a forum for the dissemination of information, and recognize advances in both academia and industry. **ACTION:** Ian Swentek asked the Board to submit any comments to him over the next few weeks.

3. Treasurers Report

• The report was submitted late and not submitted to the Board prior to the meeting for review. This report will be circulated after the meeting. It was reported that there is a delay in receiving funds from ACCE. The amount is smaller than expected and budgeted. It was noted that sponsorship to ACCE and the newsletter has declined and impacts the revenue for the Division. The budget will be reviewed at the next meeting. Ian Swentek asked the Board members to submit any new budgetary items to the Treasurer so that a budget can be prepared for the next FY.

continued on page 10...

TRAIN FOR TOMORROW ENGINEERING • MANUFACTURING • REPAIR • NDI

ENROLL TODAY!

Abaris Training is internationally recognized as the leader in advanced composite training with state of the art courses focusing on engineering, manufacturing, repair, & NDI.

www.abaris.com • +1.775.827.6568

Board Meeting Minutes continued...



This Issue:

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report

4. Committee Updates – (20 min)

- Membership: Ray Boeman reported he performed an analysis of the Division membership and this was provided in the report distributed to the Board. The report shows the lapsed members, upcoming renewals, geographic representation, and professional categories. The graphs provided a good visual to the status and trends of the Division membership. It was pointed out that the Automotive Division has similar results in their membership. The group pointed out to use the social media presence to help with membership retention and recruitment. • Education: Uday Vaidya reported the results of the 4 schools that received education grant funding for 2018. This was a very positive investment by the Division. For 2019, 3 schools were awarded grant funds for equipment. There was no update as to whether the equipment was acquired. He reported that 200-300 students so far have received benefit from this investment. It was suggested to write an article for the newsletter to demonstrate the work of the Board for students. It was pointed out that a solicitation has not been made for 2020. The group agreed that this was important, and the quantity of funds used will be based on availability from the new budget.
- **Councilor:** Dale Brosius reported that the new SPE office and facilities are a nice venue for small meetings and events. The Divisions are being asked to consider using this facility. Governance was a major topic of discussion at the Council meeting. There was much discussion about ANTEC in the planning, but given the recent events, there are changes to ANTEC that will now be a virtual meeting. He reported that other types of events like a thermoplastics conference might be a consideration.

- Audit: Ian Swentek reported that there have been no records to perform an audit. One option is to outsource this function. However the cost can vary from inexpensive to expensive. The question was asked regarding what records need to be provided for an audit. It was pointed out that both spreadsheets and Quick Book reports are being used which may complicate the process. The audit needs to include bank statements which is currently being recorded in Quick Books. This review needs to be done over the next 3 months and before the next meeting. It was suggested to contact the Automotive Division for the process they used.
- Awards: Hicham Ghossein reported the Jackie Rehkopf. awards are still under review. Over 300 applications were received with the deadline being April 1. He announced the Educator of the Year award winner. It was pointed out that there are no events planned for the PlastiVan. Dale Brosius volunteered to spearhead this initiative.
- Tech Program ANTEC: Shankar Srinivasan/Rich Caruso reported that ANTEC will be executed as a virtual program in lieu of in person due to the recent CO-VID-19 limitations. The authors are being contacted for support of a virtual program. Preliminary results indicate that it is difficult to get responses for all the speakers. It was reported that 23 presentations are in the Composites part of the conference program with one keynote. The process is very fluid at this time. They thanked the reviewers for help with the paper reviews. It was pointed out that depending on the response, there might be holes to fill in the program. It was also pointed out that the event might be expanded over a number of weeks to offset the concurrent sessions. but details are being worked out.

continued on page 11...

Board Meeting Minutes continued...



This Issue:

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report

• Newsletter: Pritam Das reported that sponsorships are down this year. The newsletter is promoted via Linked-in. He noticed that on recent posts, there have been no comments from the Board. He asked the Board to respond to all Linkedin posts to drive discussion. It was suggested that a note will be sent to the Board when items are posted. He reported that the expenses for printing the newsletter does not seem to be a good approach going forward. There are tactics that are being determined to make the marketing of the newsletter more effective. In consultation with the designer, a QR code would be developed on a single page that allows download the newsletter from scanning the code. This was tested and was going to be used at IEC, but since the event was postponed, we do not know what the success would be. Tim Johnson reported that this would cost \$30 per poster. The issue was raised to communicate the newsletter to OEMs. Ian Swentek asked Pritam Das for a proposal for the Board to consider and review at the next meeting.

5. New Business

• Ian Swentek reported that the Automotive Division is of the opinion that the ComDiv is not doing enough for ACCE. Support was requested in 3 areas: industry sponsorship, technical programming, and coordinating student sponsorships. Enamul Haque reported that he is actively participating on the planning work for ACCE every year that includes reviewing presentations and moderating sessions. The group pointed out that the ComDiv Board over the years has provided leadership and very active participation but in recent years, unilateral decisions been made without collaboration with the ComDiv representatives. It was added that the student posters have been mostly organized and driven by the ComDiv Board.

Several members volunteered to help. Ian Swentek will communicate to the Automotive Division regarding the list of activities and volunteers to help.

6. Wrap Up

- Ian Swentek will compile the Action Items and will be distributed with the minutes.
- The Next Meeting is scheduled for Tuesday, June 16, 2020 – 12:00 – 1:00 pm EASTERN (conference call).

7. Adjourn

 Ian Swentek adjourned the meeting at 1:32 pm.

Respectfully submitted, John P. Busel Secretary/Chair-Elect, SPE Composites Division Board of Directors

Attendees OFFICERS:

Ian Swentek, Chair Tim Johnson, Treasurer John P. Busel, Secretary/Chair-Elect Dale Brosius, Councilor Ray Boeman, Past Chair

DIRECTORS:

Dan Buckley Rich Caruso Michael Connolly Pritam Das Fred Deans Hicham Ghossein Jim Griffing Enamul Haque Alex Kravchenko Christoph Kuhn Marcos Pantoja Andy Rich Antoine Rios Khaled Shahwan Shankar Srinivasan Uday Vaidya

Composites Connection



Award Winning Paper

Latest Breakthroughs with Hybrid Reinforced Composites in Lightweight Applications

Dinesha Ganesarajan, Leonardo Simon Department of Chemical Engineering, University of Waterloo, Waterloo, Ontario, N2L 3G1, Canada Alper Kiziltas, Deborah Mielewski Sustainability and Emerging Materials, Ford Motor Company, Dearborn, Michigan, 48124, USA Natnael Behabtu, Christian Lenges DuPont Industrial BioSciences, Wilmington, DE, 19803, USA

Abstract

The shortage of landfill space, ocean pollution of plastics and the depletion of petroleum resources invigorated engineers and scientists to shift their focus on to the development of bio-based plastics. Natural fibers are abundant and provide many advantages such as: weight reduction, process-friendliness (no wear of tools & skin irritation), biodegradability and good acoustic insulation properties. The limitations of natural fibers as reinforcement for thermoplastics are their low mechanical properties, limited thermal stability and shrinkage in comparison to traditional inorganic reinforced thermoplastics. In this study, the objective was to develop hybrid composites combining poly -1, 3-glucan (DuPont's Nuvolve[™]) along with long glass fiber in a polypropylene matrix to optimize the overall composite properties. The polysaccharide and glass fiber loadings (wt. %) were varied and the samples were prepared via twin-screw extrusion followed by injection molding. The results showed mechanical properties decreased with increasing polysaccharide content, however there is an optimum loading of the polysaccharide that is a promising alternative to reduce the utilization of inorganic fillers (e.g. glass fiber). Thermal & morphological analyses were also conducted to understand dispersive nature of the fillers, reinforcing capability and thermal behaviour of the overall composite. In general, the composites showed enhanced thermal stability with increasing glass fiber content with good to moderate filler distribution and dispersion within the PP matrix. The hybrid reinforced thermoplastic composites can lead to vast weight and potential cost savings with the promise to advance environmental stewardship within the automotive realm.

Introduction

Petroleum-based plastics have vastly contributed to quality of life in modern society such as the advent of Polyethylene (PE) which is widely used in consumer goods, wire & cable insulation, industrial piping, linings, coatings and was historically deployed in World War II for electrical insulation of submarines and radar shields [1]. In particular, the usage of plastics by mass in the automotive industry increased from 6% in 1970 to 16% in 2010 and it is due to reach 18% by 2020 [2]. The increased usage of plastics contributes to post-consumer waste where shortage of landfill space, ocean pollution and the depletion of petroleum resources inspired engineers and scientists to develop biodegradable & renewable plastics. Next generation materials should exemplify principles of sustainability, industrial ecology and green chemistry.

continued on page 14...

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report



Fit for any environment.

Our plastics can operate in many environments, taking the requirements of any job in stride. Our innovative spirit drives the creation of next-generation lightweight material solutions capable of adapting to any specification. From flame retardancy to withstanding mechanical loads, our high-performance plastics are stronger, safer, and more effective components.

Find your next adaptable plastic at dsm.com/plastics.



Moreover, in the United States of America the corporate average fuel economy (CAFE) regulated by the national highway traffic safety administration (NHTSA) set the fuel economy standard for passenger vehicles and light-duty trucks to be 54.5 MPG by 2025 [2]. The projected added cost to a 2025 model vehicle is 1800 USD however, the improved fuel economy for those consumers who drive their vehicle for its entire lifetime would save on average 3400-5000 USD [2]. This standard further amplified the necessity for automakers to find innovative ways to improve fuel efficiency, where the concept of lightweighting sparked great interest. Newton's second law states that acceleration of an object is dependent on the forces acting upon the object and the object's mass, therefore it takes less energy

to accelerate a lighter object. Application of this fundamental law has shown that 10% reduction in vehicle weight can improve fuel economy by 6-8% [3].

Lightweighting primarily focuses on substituting heavier objects like metal with lighter materials such as carbon fiber in high performance vehicles. This is extremely hard to achieve for large volume vehicles due to the cost and metal's structural importance in the construction of engine, chassis and body exterior parts. Metals used in non-structural parts of the vehicle can be replaced with reinforced thermoplastics without compromising performance while delivering reduction in weight. Composites are attractive combin-

continued on page 15...



A member of **O ALTANA**



Ask.BYK.USA@altana.com



ing materials properties in ways not found in nature and in the automotive industry glass fibers and talc are common materials used for reinforcing plastics due to their low cost and good mechanical properties. Naturally sourced materials such as cellulose and poly -1, 3 glucan have potential to provide good reinforcing properties at a lower density (~1.5 g/cm3). The advantages of bio-based filler materials are that they provide good mechanical properties, biodegradability, lower wear on processing equipment and lower density. The limitations of such materials are their restricted thermal stability, shrinkage in comparison to traditional inorganic fillers, hydrophilic nature of the filler and higher than usual cost/pound of material in comparison to inorganic fillers. Therefore, completely replacing inorganic filler material with naturally sourced material is not viable in today's economic environment, however combining inorganic and bio-based fillers could provide an intermediate and necessary solution to achieving performance properties, lightweighting and biodegradability.

This Issue:

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report

Sponsor the Newsletter

The best advertising value in the Composites Industry

- Support your SPE Composites Division
- Reach 1,000 Composites Professionals 3 Times a year via the E-Newsletter
- Maximize your exposure to the customers & the trade

Contact Teri Chouinard CBC, APR for more info Teri@IntuitGroup.com

See page 26 for more details



Improvements to fuel efficiency are initial steps to achieving a circular economy. However, there is also a need for a holistic approach to engineering design for next generation automotive parts that consider the source of materials, processing and disposal at end of usage which all contribute to the total carbon footprint associated per vehicle production.

The purpose of this research was to develop hybrid composites combining polysaccharides of unique morphologies with glass fiber in a polypropylene matrix. In particular, DuPont's poly α -1,3 glucan (derived from sucrose feedstock) to reinforce polypropylene in combination with glass fiber for body interior and underhood applications such as IP substrate. center console and battery cover in passenger vehicles & light-duty trucks. Composites were produced at various loadings of polysaccharide and glass fiber using melt blending (twin screw extruder) and injection molding. The effect of the combination of filler loading on the composite properties were investigated (mechanical and thermal) to gain insight of strategies to optimize performance properties of the composites. This research attempts to provide a comprehensive study on the development of hybrid composites containing naturally sourced materials to deliver optimum mechanical and thermal properties suited for body interior and underhood applications for passenger vehicles and light-duty trucks while achieving significant lightweighting opportunities.

The major challenge of incorporating polysaccharides in polypropylene matrix is surface compatibility due to the hydrophilic and hydrophobic nature of polysaccharides and polypropylene. Filler-matrix adhesion is critical, as the role of the matrix in a fiber-reinforced plastic is to transfer the load to the

continued on page 16...



stiff fibers through shear stresses at the interface; which requires good adhesion. It is desired to have strong binding capabilities between the filler and the matrix and having weak binding sites promotes void structures and particle agglomeration. Therefore, it is essential to maximize the interfacial compatibility of the filler within the continuous polymer matrix.

Experimental

Polypropylene (PP) homopolymer pellets, long glass fiber filled PP pellets were provided by local suppliers and poly -1,3-glucan of two particles sizes (5 & 20 microns) were supplied by DuPont Industrial BioSciences under the tradename NuvolveTM. Polypropylene grafted maleic anhydride (PP-g-MA: locally sourced) was used as a coupling agent to help with the compatibility of hydrophobic PP and hydrophilic polysaccharide.

The composites were prepared using a twostep process i) extrusion and ii) injection molding. Nuvolve[™] masterbatch (30%) with PP was compounded using twin-screw extruder (ThermoHaake Rheomex Model PTW25) and prior to extrusion all materials were dried to reduce moisture content using an oven at 60°C for 12 hours. The dry PP, PP-g-MA and Nuvolve[™] were separately starve-fed into a twin screw extruder via K-Tron gravimetric feeders. After extrusion, the materials were immediately quenched in a water bath and kept at room temperature. The compounded materials from the twin screw extruder were granulated using a lab scale grinder/chopper and dried at 60°C 12 hours before the injection molding step.

Nuvolve[™] masterbatch (30%) with PP (now grounded pellets) was hand-mixed with long glass fiber filled PP pellets and then transferred to the injection molder (Boy Machines Model 80M) to process ASTM test specimens for tensile (ASTM-D638-10), flexural (ASTM D790-10) and impact (ASTM D256 – 10) testing, respectively.

Table 1 shows the formulations used in this study, where two particle sizes of DuPont's NuvolveTM (Nuv A=5 microns, Nuv B=20 microns) were supplied and the control samples used were 5% & 10% glass fiber reinforced PP, virgin PP and Ford's incumbent material (35% total filler content). It is also important to emphasize the exclusion of a second extrusion step to incorporate the

glass fiber in the Nuvolve[™] masterbatch (30%) with PP. The elimination of a second extrusion process can speed up part production, lower manufacturing costs and reduce thermal degradation and fiber attrition.

continued on page 17...

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report



Sample Code	Nuvolve™ A (wt. %)	Nuvolve™ B (wt. %)	Glass Fiber (wt. %)	Total Filler (wt. %)
Neat PP				
5%GF_PP		1000	5	5
10%GF_PP			10	10
10/10-A	10		10	20
10/15-A	10		15	25
10/20-A	10		20	30
15/15-A	15		15	30
20/10-A	20		10	30
10/10-B		10	10	20
10/15-B		10	15	25
10/20-B		10	20	30
15/15-B		15	15	30
20/10-B		20	10	30



This Issue:

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report



Mechanical Test & Density Measurement

Tensile, flexural and impact tests were conducted using a universal testing machine (Instron 3366) and a pendulum tester (Testing Machines Inc. 43-02-03 model) in compliance with ASTM D638-10, ASTM D790-10 and ASTM D256 – 10, respectively. The properties of interest were: tensile strength, strain, young's modulus, flexural modulus, maximum flexural stress and impact resistance. All mechanical tests were run in an environmentally conditioned room at 23°C± 2°C and 50± 5% relative humidity. Density was measured using an analytical balance (readability down to 0.1mg) and density kit ME-DNY-43 from Mettler Toledo.

Thermal Characterization

Thermal transitions of the composites and the neat polymer matrix were analyzed using a differential scanning calorimetry instrument (DSC: TA Instruments Q2000). At first the samples were heated from room temperature to 190°C at a rate of 50°C/ min and isothermally held for five minutes. Thereafter, the samples were cooled to 70°C at 10°C/min and isothermally held for 5 minutes before reheating to 190°C at 10°C/ min. The melting and crystallization transitions were collected from the heat flow versus temperature curves where, melting temperature (T_m) is an endothermic transition and the crystallization temperature (T_c) is an exothermic transition denoted by the peak minimum and maximum respectively. Heat of fusion (ΔH_m) and enthalpy of crystallization (ΔH_{a}) were also calculated.

Thermal gravimetric analysis (TGA: TA Instruments Q500) was used to study thermal stability of neat PP and the composites. The samples were heated at 20°C/min and subjected to nitrogen from room temperature to 800°C and then held isothermally in air for five minutes. The degradation temperature of the resin and fillers can be identified from TGA.

Morphology (SEM)

Zeiss 1550 (LEO) scanning electron microscope with accelerating voltage of 5-7.keV was used to observe the morphology of the composites and the neat PP as well as distribution of fillers within the polymer matrix. The samples were cut using a paper cutter (guillotine) exposing fracture surface of the samples Furthermore the samples were sputtercoated with gold to avoid surface charging.

Results and Discussion Mechanical Properties Tensile Properties & Density Measurement

The effects of different fiber combinations on the tensile properties of the composites and control samples which include neat PP, PP filled with glass fiber (5 &10%) and Ford Motor Company's incumbent material are showcased in Figure 2, 3 and 4. The composites are labelled as 10/10, 10/15 and etc. where, the first number represents Nuvolve™ content and the latter represents glass fiber content. Overall, the addition of inorganic and natural fillers led to a considerable increase in the tensile strength at maximum load and young's modulus. The inorganic filler (glass fiber) had a greater improvement in strength and modulus values compared to poly α -1,3glucan (DuPont's Nuvolve[™]); an increase of 122% and 190% for tensile strength at maximum load and modulus respectively was observed for Nuvolve™/GF (10/20) composites compared to neat PP. Note that 30/0 formulation that only contained Nuvolve™ as a filler performed poorly in tensile strength (16% decrease), however improved modulus (29% increase) when compared to neat PP. It is expected that glass fiber improves tensile strength and modulus at a higher factor than naturally sourced materials due their strong and stiff mechanical properties. The strongest performer of the hybrid composites was

continued on page 18...



10/20 formulation followed by 10/15 and 10/10 formulations which utilizes 20-25% of total filler content in comparison to Ford's incumbent material (35% total filler content). Figure 1, shows the density reduction (%) compared to Ford's incumbent material that is being used for body interior and underhood applications; where formulations 10/15 and 10/20 show a density reduction of 13 and 10% respectively. Therefore, the combination of inorganic and naturally sourced filler materials can offer enhanced mechanical properties with sufficient weight savings per vehicle part.



Figure 1: Density Reduction (%) of all composites and neat PP in reference to Ford Incumbent Material



Figure 2: Tensile Strength (MPa) of composites and neat PP

The tensile strains at maximum load of the composites were lower than neat PP (Figure 4) with no considerable difference in strain as a function of total, inorganic and natural filler content.





Overall the tensile properties showed that there is a greater influence in performance via the addition of glass fibers compared to DuPont's NuvolveTM, however hybridization of both fillers produced beneficial enhancements in performance and lightweighting.



Figure 4: Tensile Strain (%) of composites and neat PP

Flexural Properties

Flexural properties exhibited a similar trend as the tensile results, showing that the addition of glass fibers had a positive impact on the modulus and maximum stress.

continued on page 19...

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report





This Issue:

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report



Award Winning Paper continued...



Figure 5: Flexural Modulus (MPa) of all composites and neat PP



Figure 6: Maximum Stress (MPa) on all composites and neat PP

The addition of DuPont's Nuvolve[™] showed a 22% increase in modulus (Figure 5) compared to neat PP and the highest performing composite 10/20 had an overall increase of 193% in modulus and 74% in maximum stress (Figure 6) compared to neat PP. Ford's incumbent material has a modulus of 3600 MPa and the 10/15 formulation was able to meet the requirement. It should be noted that there is no official requirement listed for maximum stress and hence Ford Motor Company does not specify an official value for this metric.

Impact Properties

Figure 7 shows that impact resistance decreased by 54% for formulation 30/0 and this can be attributed to the dispersive nature of the material as well as promoting stress concentrations within the polymer matrix. This is consistent with Panthapulakkal and Sain's [4] findings, where they found hemp/glass fiber PP composites had enhanced impact resistance with an increase of glass fiber content. Moreover, the hybrid composites had an increase in impact resistance up to 123% (10/20) compared to Neat PP and this is largely attributed to glass fiber content. It can also be noted that the 10/10 formulation meets and exceeds Ford's incumbent material requirement by 50% and showcases a density reduction of 17% (Figure 1). Therefore, the hybrid composites are able to provide superior impact resistance while offering lightweighting opportunities.



Figure 7: Impact Resistance (kJ/m^2) of all composites and neat PP

continued on page 20...

Overall, the addition of DuPont's Nuvolve™ and glass fiber in a PP matrix enhanced mechanical performance. The greatest contributing factor is the concentration of glass fiber in the composite, however the addition of Nuvolve[™] also provides for enhanced mechanical properties (to a lesser degree) while offering superior weight savings per material part. 10/15 formulation was the optimal solution as it was able to meet Ford's incumbent material specification with the exclusion of tensile strain. Furthermore, this formulation showed a density reduction of 13% compared to Ford's incumbent material, showcasing lightweighting opportunities in non-structural components of an automobile.



Figure 8: Onset Decomposition Temperature of NuvolveTM A

Thermal Properties

The mechanical properties showed no clear distinction in performance between Nuv-A and Nuv-B. Nuv-B has a particle size of 20 microns (4 times larger than Nuv-A) and it costs less to manufacture indicating commercial potential. Consequently thermal and morphological data are presented with respect to Nuv-B. Figures 8, 9, 10 and 11 summarizes the thermal stability of the composites and neat PP, demonstrating the onset decomposition temperature of Nuvolve[™] & Polypropylene (TdN, TdP) and temperatures at 10% & 15% weight loss from TGA curves. The crystallization & melting temperatures are presented in Figures 12 & 13 along with values for heat of fusion and crystallization in Table 2.



Figure 10: Temperature at 10% weight loss from TGA curves



Figure 11: Temperature at 15% weight loss from TGA curves

continued on page 21...

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report



Figure 9: Onset Decomposition Temperature of PP





Figure 12: Crystallization Temperature (T_c)

Figure 8 shows that the decomposition of Nuvolve[™] is consistent and does not fluctuate, formulation 30/0 consisting of only NuvolveTM showed the lowest value and there is a slight positive correlation with the addition of glass fiber in the composites (5.8% increase). The onset degradation temperature of PP gradually increased, formulation 30/0 showed a 26% increase with respect to neat PP. Moreover, the temperatures at which 10% and 15% weight loss (Figures 10 & 11) occurred were also used to evaluate thermal stability. The hybrid composites were more stable than neat PP with the glass fiber having a greater influence. Formulation 30/0 showed a 15% decrease in temperature compared to neat PP.





Figures 12 and 13 summarize the crystallization (T_c) and melting temperatures (T_m) of the control samples and the composites. The crystallization temperature decreased for all composites with respect to neat PP. This could outline the possibility of the Nuvolve[™] and the glass fiber not being able to act as nucleating agents to aid in faster crystallization of the PP. On average there is a 3% decrease in crystallization temperature of all composites relative to neat PP. The melting temperature increased for all composites in comparison to neat PP (5% increase), however the effect of Nuvolve™ is minimal on the melting temperature which stayed consistent for all composites.

Enthalpies from DSC					
Sample Code	<u>Heat of Fusion ∆H_f (J/g)</u>	Enthalpy of Crystallization ΔH_{c} (J/g)			
Ncat PP	139.20	129.9			
0/5	100.70	98.72			
0/10	143 40	129			
30/10	81.11	91.99			
10/10	106.90	115.2			
10/15	96.86	102.1			
10/20	91.11	97.31			
15/15	103.50	102.71			
20/10	99.83	102.9			

Table 2: Enthalpies of crystallization and melting for neat PP and composites

This Issue:

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report



continued on page 22...



Overall, the composites showed enhanced thermal stability in comparison to neat PP. The integration of Nuvolve[™] did not profoundly increase thermal stability of the composites, glass fiber had a greater influence. However, combining both materials showed that the composites were thermally stable (compared to neat PP) with the upside of potential cost effectiveness in regards to weight savings per automotive part. The DSC results showed that the fillers do not act as nucleating agents to aid with accelerated crystallization which translates to a potential increase in part production and reduction in cycle times. The melting temperature increased for all composites compared to neat PP but, there was minimal differences across the composites alluding to the little influence of individual fillers on the melting temperature. Table 2, shows the enthalpies of crystallization and melting and the general trend observed is that the composites have decreased values compared to neat PP when incorporating Nuvolve[™] as opposed to glass fiber. Generally, the thermal properties show that the hybrid composites can be utilized in challenging conditions e.g. underhood applications offering thermal stability.



Figure 14: SEM micrograph of Neat PP at 100x magnification

Morphological Properties

Formulations 10/10, 10/15 and 10/20 were the best performers with respect to mechanical and thermal properties and therefore are demonstrated in this section. Figures 14, 15, 16, 17 and 18 show SEM images at 100x magnification of neat PP and the hybrid composites with the following filler loading: 30/0, 10/10, 10/15 and 10/20.

Figure 15 shows that Nuvolve[™] is evenly distributed and dispersed in the continuous PP matrix, where no clear distinction can be concluded to separate filler from matrix. Figures 16 and 17 show good distribution of glass fiber in regards to formulation 10/15 and 10/20, therefore the reinforcement capability is maximized as seen in their respective mechanical performance. In Figure 19, the micrograph shows Nuvolve™ without the addition of glass fiber in the PP matrix and it can be observed that the poly -1, 3-glucan forms agglomeration of particles with an average size of 30 microns which translates to poor transfer of load between filer and matrix. Furthermore, the dark shadows around the particles indicate poor adhesion between the Nuvolve $\ensuremath{^{\mathrm{TM}}}$ and the continuous polymer phase.

Figures 19, 20, 21, 22 show micrographs where glass fiber can be distinguished from Nuvolve[™] by their difference in diameter and shape (Figure 20). Overall good dispersion and moderate distribution is observed for the hybrid composites. Poly -1, 3-glucan and polypropylene are hydrophilic and hydrophobic by nature, and therefore it is difficult to attain good adhesion at the interface between the filler and matrix. Good to moderate adhesion is directly related to the composite's mechanical performance as the filler's sole duty is to effectively transfer load from the polymer matrix.

continued on page 23...

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report







Figure 15: SEM micrograph of 30/0 formulation at 100x magnification



Figure 16: SEM micrograph of 10/10 formulation at 100x magnification



Figure 18: SEM micrograph of 10/20 formulation at 100x magnification



Figure 19: SEM micrograph of 30/0 formulation at 500x magnification



Figure 20: SEM micrograph of 10/10 formulation at 500x magnification

continued on page 24...

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report





Figure 17: SEM micrograph of 10/15 formulation at 100x magnification





Figure 21: SEM micrograph of 10/15 formulation at 500x magnification



Figure 22: SEM micrograph of 10/20 formulation at 500x magnification

In Figure 21, fiber pull-out is observed, which is good indication of poor adhesion between the filler and continuous polymer matrix.

Overall, the hybrid composites exhibit moderate to good filler distribution and dispersion. Interfacial adhesion can be improved in the processing of the composites such as double extrusion instead of hand-mixing of glass fiber before the injection molding step. Melt Blending (extrusion) is known to be an effective dispersive technique to incorporate fillers and it is expected that a second extrusion step would aid in greater dispersion of the filler. However, this would add costs to the overall part and the mechanical and thermal properties showed that the current methodology is good enough to be employed on non-structural components in body interior and underhood applications.

continued on page 25...

This Issue:

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report



The best advertising value in the Composites Industry

- Support your SPE Composites Division
- Reach 1,000 Composites Professionals 3 Times a year via the E-Newsletter
- Maximize your exposure to the customers & the trade



Contact Teri Chouinard CBC, APR for more info Teri@IntuitGroup.com See page 26 for more details



This Issue:

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report



Summary and Recommendations

In this study, the development of hybrid composites were investigated utilizing DuPont's Nuvolve[™] and glass fiber as fillers in a PP polymer matrix . The maximum total filler content did not exceed past 30 wt. % and the mechanical, thermal and morphological properties were evaluated and compared to Ford's incumbent material, neat PP and 5 %10% glass fiber filled composites for body interior and underhood applications in passenger vehicles and light-duty trucks.

The mechanical properties of the composites showed general increase in performance with glass fiber content and the opposite with Nuvolve[™] content. However, optimum formulations were found (10/15, 10/20) that may reduce or replace a portion of the inorganic content. The best performing composites were 10/15 and 10/20 which outperformed Ford's incumbent material; creating an opportunity for a reduction up to 10% in total filler content and up to 13% in density per automotive part.

The thermal stability of the composites showed improvements in comparison to neat PP, where glass fiber had a more dominant role than Nuvolve[™]. The crystallization temperature (Tc) of the composites decreased revealing that Nuvolve[™] is not a nucleating agent that could speed up crystallization during processing and subsequently decreasing cycle time. Overall, the composites showed improved thermal stability and can potentially be utilized in challenging environments such as underhood applications.

Morphology takes a deep dive into fillermatrix interactions which are pivotal for performance of the composites. DuPont's Nuvolve[™] is a polysaccharide that is hydrophilic by nature and the PP is hydrophobic which highlights incompatibility issues. Therefore, having good distribution and adhesion of fillers are crucial to attain superior performance properties. The SEM micrographs showed that the best performing composites in this study (10/15 &10/20) had good to moderate filler distribution and adhesion with the continuous polymer matrix. There are localized areas with dark shadows around glass fiber and Nuvolve[™] particles along with fiber pull-out showing glimpses of poor adhesion. This can be improved by adding a greater concentration of maleic anhydride or the addition of a second melt blending step.

The hybridization of Nuvolve[™] with glass fiber yields high performing composites that can be exploited in body interior and underhood applications for passenger vehicles and light-duty trucks. The composites use up to 10% less filler material and demonstrate a density reduction of up to 13%; contributing to weight savings and also positively impacting the sustainability effort by incorporating a biodegradable material.

Acknowledgements

The co-authors and I would like to thank the Sustainability and Emerging materials group at Ford Motor Company that contributed to this work especially Daniel Frantz and Sandeep Tamrakar. We would also like to thank DuPont Industrial Biosciences for suppling raw material and the University Of Waterloo & Ford Motor Company for sponsoring this study.

continued on page 26...



Bibliography

- B. Fry, Working with Polyethylene (Speaking of Plastic Manufacturing), Dearborn: Society of Manufacturing Engineers, 1999.
- [2] L. Miller, K. Soulliere, S. Beaulieu, S. Tseng and E. Tam, "Challenges and Alternatives to Plastics Recycling in the Automotive Sector," Materials, pp. 5883-5902, 2014.
- [3] A. Buchenauer, "Wood Fiber Polyamide Composites for Automotive Applications," University Of Waterloo, Waterloo, ON Canada, 2016.
- [4] S. Panthapulakaal and M. Sain, "Injectionmolded short hemp fiber/glass fiber-reinforced polypropylene hybrid composites— Mechanical, water absorption and thermal properties," Jounnal of Applied Polymer Science, vol. 103, no. 4, pp. 2432-2441, 2007.
- [5] Department of Transportation (National Highway Traffic Safety Administration), "2017 and Later Model Year Light-Duty Vehicle Greenhouse Gas Emissions," Federal Register, vol. 77, no. 199, pp. 62623-63200, 2012.

- [6] A. Birch, C. Dal Castel, D. Mielewski, L. Simon and A. Kiziltas, "Development of cost effective and sustainable polyamide blends for automotive applications," in SPE ACCE, Troy, MI, 2015.
- [7] A. Kiziltas, J. Gardner, Y. Han and H. Yang, "Mechanical Properties of Microcrystalline Cellulose (MCC) Filled Engineering Thermoplastic Composites," Journal of Polymers and the Enviroment, vol. 22, no. 3, pp. 365-372, 2014.
- [8] A. Mohanty, M. Misra and L. Drzal, Natural Fibers, Biopolymers, and Biocomposites, Boca Raton: CRC Press Taylor & Francis Group, 2005.
- [9] A. Langhorst, J. Burkholder, J. Long, R. Thomas, A. Kiziltas and D. Mielewski, "Blue-Agave Fiber-Reinforced Polypropylene Composites for Autmotive Applications," BioResources, vol. 13, no. 1, pp. 820-835, 2018.

Sponsor the Newsletter

This Issue:

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report



3.75" x 5"	\$500
Half page ad: 7.5" x 5.5", 5" x 7.5", 4" x 8.5"	\$750
Full page ad: 7" x 10", 8.5" x 11"	<mark>\$1,250</mark>
Contact: Teri Chouinard CBC, APR SPE Composites Division	

Quarter page ad or logo ad:

SPE Composites Division Sponsorship Chair C/O Intuit Group, Inc. phone 248.701.8003 Teri@IntuitGroup.com

Please provide Logos as JPG and EPS files (send both if possible) Please provide Ads as High Resolution PDF files Advertising with the SPE Composites Division is inexpensive and easy. Please help us to promote the benefits of Composites in Industry.

Sponsoring the Newsletter enables the SPE to communicate the benefits of the composites in many industries, which fortifies your marketing efforts.

Composites Connection

- Support your SPE Composites Division
- Reach 1,000 Composites Professionals 3 Times a year via the E-Newsletter
- Also reach 1,070 SPE Composites Division Linked In Members 3 times a year and an additional 11,492 COMPOSITES Linked In Members Secondary group where the link to the newsletter is posted year-round
- Reach many more as a sponsorship also includes your logo on our website, www.composites.4speorg with a link to your company
- Maximize your exposure to the customers & the trade
- · Stay informed on the latest composites activity

Increase your presence on the web leading to more sales by sponsoring our Electronic Newsletter which is published on the SPE Composites Division Website and emailed to all Division Members (1,000 approx.) 3 times annually. Rates include 3 issues (not on calendar basis - published approx. Nov/Dec, Mar/April, July/August). All ads include a link to your website increasing your exposure on the worldwide web exponentially. Sponsorship also includes your logo ad with a link to your website on <u>www.composites.4speorg</u> further increasing your presence on the Web as a Leader in Composites Technology.

Councilor Report



By: Dale Brosius

- 1. Last Council meeting was held virtually on March 27th, replacing the council meeting that was due to be held in person the weekend prior to ANTEC.
- 2. SPE continues to evolve, and numerous bylaw changes were necessitated by the decision taken in November to vest full day to day decision making with the Executive Board of SPE. These were approved in short order.
- At the September virtual Council meeting, it was presented that the EB was considering changes to some of the VP positions to better align with today's needs. With the decision at the Fall meeting in Danbury to keep the EB at the current number, the EB decided to move forward with this re-alignment.



4. Elections for the new position of VP Sustainability and 2020-2020 officers were completed on 6/10/2020 for terms starting July 1, 2020. The VP Sustainability position had four nominees and required three rounds of voting. Results of voting are:

President-Elect VP Business & Finance VP Sustainability

Jason Lyons Ed Trueman Conor Carlin

In addition, the Council elected a chair for the Council Committee of the Whole, and the winner was Barry Morris of Dow Chemical.

Current President-Elect Jaime Gomez will ascend to the role of President of the Society on July 1 when Brian Landes term ends.

VP Marketing & Communications	>	VP Sustainability		
VP Technoloty & Education>		VP Publications		
VP Events	>	VP Professional Development		
VP Young Professionals	>	VP Member Engagement		
VP Sections	>	VP Chapters		
VP Divisions	>	VP Appointed		
VP Business & Finance		Unchanged		

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report





Membership Report



By: Ray Boeman

(Data from current as of June 9,2020)



494 Active members as of June 9,2020, a decrease of 16 from last report (March 13, 2020). However, new young professinoals increased by 100% from March to June.

Membership Categories

	June 2020			March 2020		
Professional:	309	62%		321	63%	
Student:	97	20%		120	24%	
New Young Prof:	43	9%		22	4%	
Emeritus:	24	5%		23	5%	
Young Prof:	19	4%		22	4%	
Distinguished:	2	<1%		2	<1%	



With our diverse portfolio of innovative, high performance engineered polymers and polypropylene resins, we can provide you the tools you need to create products for a better tomorrow.





Awards Report



This Issue:

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report



e sure to check out the SPE Composites Division booth at ANTEC 2020 St. Antonio TX for further information on our awards programs.

- 1. Harold Giles Award 2020: This year, a total of 27 applicants are under review from 11 volunteers. The review round is due by June 25th and by July 1st we must get back to SPE Foundation with the name of the awardees. So far the award amount for both the Graduate and Undergraduate students is set to \$3500 and a \$1000 check used to be issued toward the endowment funds. This award is administered through the SPE Foundation. Information about the award and application process can be found on the foundation website at: http:// www.4spe.org/Foundation/
- 2. Jackie Rehkopf Scholarship 2020: The SPE Foundation have revised their scholarship agreement and it is attached to this report, in addition to the spending policy, for revision by the Composite division directors. As of June 9th, 2020, the available funds are \$66,825. If we move toward endowment the annual payout would be \$2,840 - \$3,341 depending on market conditions. Details of the fund build up can be found in attached presentation. In order to reach the \$100k endowment fund we need to maintain the same contribution for another 3 years. Then the SPE Foundation Spending Policy would pay out between \$4,250 and \$5,000 annually depending on the market when the Fund reached its goal of \$100k. Note that the Jackie Rehkopf Scholarship is jointly funded by both Automotive and Composites Divisions. Initially there were two awards of \$5000 each, however the awards committee thereafter decided to



reduce to a single award and build the account reserves more quickly to achieve an endowment level. Therefore, with an annual commitment from Automotive of \$5000 and from Composites of \$6000, and an award level presently maintained at \$5000, we are building the fund by an additional \$6000 again this year.

- 3. **METTLER TOLEDO Award 2020:** Also known as the travel award. This award is dependent on the status of conferences regarding the Covid-19 situation.
- 4. **Sabic Educator of the Year Award 2020:** This award recognizes outstanding contribution toward educating the next generation of composites professionals. Dr. Tate was selected for this year. Sabic is confirming the amount of sponsorship they can cover toward the award this year. We should have a number from them by the time of the meeting next year. The normal award is \$2500 normally presented with a plaque at ANTEC. This year we will have to mail it to the recipient as ANTEC was held online.
- 5. Honored Service Member / SPE Fellow: We haven't selected candidates for the 2019-2020 calendar year yet. The nomination forms were due in October/November time frame. But I have not received any.

I would like to say a word of thanks to the many volunteers helping solicit and adjudicate the awards this year. Your support enables the continued success of these scholarship programs.

Kind Regards, Dr. Hicham Ghossein



Treasury Report

By: Tim Johnson, Treasurer



urrently the Division has cash on the order of \$28.6K and \$115.3K in investment. This reflects distribution to the SPE Foundation of \$12K for scholarship funding for the new fiscal year.

In consideration of reduced income from ACCE 2019, and present projections for a very challenging ACCE 2020, the board has adopted a budget for the coming fiscal year with significant cost reductions while retaining the full funding of our two scholarships administered through the SPE Foundation along with two days of support for Plastivan.

Based upon a potential scenario of ACCE 2020 reduced to break-even, and despite cost reductions, the proposed budget for fiscal year 20/21 projects a deficit of \$15.2K

which represents approximately 13.2% of investment fund reserves.

A financial year-end summary for FY 19/20 along with the approved budget for FY 20/21 is provided as a separate file. With a reduction of expenses associated with ANTEC and Plastivan, plus SPE Rebates not originally included in the previous budget, the net deficit for FY 19/20 was substantially lower than forecast.

I look forward to the forthcoming board meeting to discuss the current projections for our first Virtual ACCE, and any other financial adaptations we may need to consider for the coming year.

Tim Johnson SPE Composites Division Treasurer

This Issue:

- Chair's Message
- BOD Listings
- Board Meeting Minutes
- Award Winning Paper
- Councilor Report
- Membership Report
- Awards Report
- Treasurer Report



The best advertising value in the Composites Industry

- Support your SPE Composites Division
- Reach 1,000 Composites Professionals 3 Times a year via the E-Newsletter
- Maximize your exposure to the customers & the trade



Contact Teri Chouinard CBC, APR for more info Teri@IntuitGroup.com See page 26 for more details